



Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	188 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>184</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>		kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>		-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>3,9</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>3,86</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,3</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,18</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>NA</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>2</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>2</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,99</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-		<b>2,787</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-		<b>NA</b>	m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>1630</b>	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class		Water heating energy efficiency	$\eta_{wh}$	NA	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>NA</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>NA</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

## Warm climate and Low temperature

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	247 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	$P_{rated}$	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>243</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	$P_{dh}$		kW	T <sub>j</sub> = -7 °C	$COP_d$		-
T <sub>j</sub> = +2 °C	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = +2 °C	$COP_d$	<b>3,40</b>	-
T <sub>j</sub> = +7 °C	$P_{dh}$	<b>3,5</b>	kW	T <sub>j</sub> = +7 °C	$COP_d$	<b>5,00</b>	-
T <sub>j</sub> = +12 °C	$P_{dh}$	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	$COP_d$	<b>8,51</b>	-
T <sub>j</sub> = bivalent temperature	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = bivalent temperature	$COP_d$	<b>3,40</b>	-
T <sub>j</sub> = operation limit temperature	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = operation limit temperature	$COP_d$	<b>3,40</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	$P_{dh}$	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	$COP_d$	<b>NA</b>	-
Bivalent temperature	$T_{biv}$	<b>2</b>	°C	For air-to-water heat pumps: Operation limit temperature	TOL	<b>2</b>	°C
Cycling interval capacity for heating	$P_{cych}$	<b>NA</b>	kW	Cycling interval efficiency	$COP_{cyc}$	<b>NA</b>	-
Degradation co-efficient	$C_{dh}$	<b>0,98</b>	-	Heating water operating limit temperature	WTOL	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	$P_{OFF}$	<b>0,015</b>	kW	Rated heat output (*)	$P_{sup}$	<b>0,0</b>	kW
Thermostat-off mode	$P_{TO}$	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	$P_{SB}$	<b>0,015</b>	kW				
Crankcase heater mode	$P_{CK}$	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-		<b>2787</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	$L_{WA}$	<b>NA / 46</b>	dB	-		<b>NA</b>	m <sup>3</sup> /h
Annual energy consumption	$Q_{HE}$	<b>1237</b>	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class		Water heating energy efficiency	$\eta_{wh}$	NA	%
Daily electricity consumption	Q <sub>elec</sub>	<b>NA</b>	kWh	Daily fuel consumption	Q <sub>fuel</sub>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>NA</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsvägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

240520

**Average climate and Medium temperature**

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	155 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>5</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>151</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>4,4</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>2,43</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,7</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>3,82</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,0</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>4,85</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,16</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,14</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,14</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>NA</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-10</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-10</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>2687</b>	kWh				

For heat pump combination heater:

Declared load profile	NA	Efficiency class	NA	Water heating energy efficiency	$\eta_{wh}$	NA	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>NA</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>NA</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Box 309, SE-341 26 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

231206

## Average climate and Low temperature

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	202 %
Equipped with a supplementary heater:	No	Package efficiency class:	A+++ -
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>5</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>198</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>4,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,30</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,9</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,99</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>6,24</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>8,00</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,0</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,0</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>NA</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-10</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-10</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,97</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>2176</b>	kWh				

For heat pump combination heater:

<b>Declared load profile</b>	<b>NA</b>	<b>Efficiency class</b>	<b>NA</b>	<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>NA</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>NA</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>NA</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Box 309, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

231206



Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	138 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>134</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>3,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,28</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,0</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>5,21</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,45</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,3</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,23</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>3,1</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>1,57</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>4,1</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>2,09</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-13</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-22</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>2,9</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input	<b>Electric</b>		
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW				
Other items							
Capacity control	<b>Variable</b>			For air-to-water heat pumps: Rated air flow rate, outdoors	-	<b>2787</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	<b>NA</b>	m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>4316</b>	kWh				

For heat pump combination heater:							
<b>Declared load profile</b>	<b>NA</b>	<b>Efficiency class</b>	<b>NA</b>	<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>NA</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>NA</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>NA</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoAir 708M + CTC EcoLogic		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	171 %
Equipped with a supplementary heater:	No	Package efficiency class:	-
Heat pump combination heater:	No		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>167</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>3,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,63</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,3</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>5,20</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>6,74</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>8,04</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,89</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>3,6</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,25</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>4,4</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>2,69</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-13</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-22</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>2,4</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3484</b>	kWh				

For heat pump combination heater:				For heat pump combination heater:			
<b>Declared load profile</b>	<b>NA</b>	<b>Efficiency class</b>	<b>NA</b>	<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>NA</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>NA</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>NA</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	188 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>184</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>		kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>		-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>3,9</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>3,86</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,3</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,18</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,8</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,58</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>NA</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>2</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>2</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,99</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>1630</b>	kWh				

For heat pump combination heater:

<b>Declared load profile</b>	<b>XL</b>	<b>Efficiency class</b>		<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>116</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>7</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	<i>AEC</i>	<b>1445</b>	kWh	Annual fuel consumption	<i>AFC</i>	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



## Warm climate and Low temperature

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	247 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	$P_{rated}$	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>243</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	$P_{dh}$		kW	T <sub>j</sub> = -7 °C	$COP_d$		-
T <sub>j</sub> = +2 °C	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = +2 °C	$COP_d$	<b>3,40</b>	-
T <sub>j</sub> = +7 °C	$P_{dh}$	<b>3,5</b>	kW	T <sub>j</sub> = +7 °C	$COP_d$	<b>5,00</b>	-
T <sub>j</sub> = +12 °C	$P_{dh}$	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	$COP_d$	<b>8,51</b>	-
T <sub>j</sub> = bivalent temperature	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = bivalent temperature	$COP_d$	<b>3,40</b>	-
T <sub>j</sub> = operation limit temperature	$P_{dh}$	<b>5,7</b>	kW	T <sub>j</sub> = operation limit temperature	$COP_d$	<b>3,40</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	$P_{dh}$	<b>NA</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	$COP_d$	<b>NA</b>	-
Bivalent temperature	$T_{biv}$	<b>2</b>	°C	For air-to-water heat pumps: Operation limit temperature	TOL	<b>2</b>	°C
Cycling interval capacity for heating	$P_{cych}$	<b>NA</b>	kW	Cycling interval efficiency	$COP_{cyc}$	<b>NA</b>	-
Degradation co-efficient	$C_{dh}$	<b>0,98</b>	-	Heating water operating limit temperature	WTOL	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	$P_{OFF}$	<b>0,015</b>	kW	Rated heat output (*)	$P_{sup}$	<b>0,0</b>	kW
Thermostat-off mode	$P_{TO}$	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	$P_{SB}$	<b>0,015</b>	kW				
Crankcase heater mode	$P_{CK}$	<b>0,000</b>	kW				
Other items							
Capacity control	<b>Variable</b>			For air-to-water heat pumps: Rated air flow rate, outdoors	-	<b>2787</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	$L_{WA}$	<b>NA / 46</b>	dB	For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger	-	<b>NA</b>	m <sup>3</sup> /h
Annual energy consumption	$Q_{HE}$	<b>1237</b>	kWh				

For heat pump combination heater:

<b>Declared load profile</b>	<b>XL</b>	<b>Efficiency class</b>		<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>116</b>	%
Daily electricity consumption	Q <sub>elec</sub>	<b>6,570</b>	kWh	Daily fuel consumption	Q <sub>fuel</sub>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>1445</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsvägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

240520



**Average climate and Medium temperature**

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	155 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A+++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>5</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>151</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>4,4</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>2,43</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,7</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>3,82</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,0</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>4,85</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,16</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,14</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,14</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-10</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-10</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>2687</b>	kWh				

For heat pump combination heater:

Declared load profile	XL	Efficiency class	A	Water heating energy efficiency	$\eta_{wh}$	99	%
Daily electricity consumption	Q <sub>elec</sub>	<b>7,700</b>	kWh	Daily fuel consumption	Q <sub>fuel</sub>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>1694</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsvägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

231206

**Average climate and Low temperature**

Ljungby

Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	A+++ -
Water-to-water heat pump:	No	Controller class:	VI -
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	202 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	A+++ -
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>5</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>198</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>4,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,30</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,9</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,99</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>6,24</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>8,00</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>5,0</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>5,0</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>na</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>na</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-10</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-10</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,97</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>0,0</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>2176</b>	kWh				

For heat pump combination heater:

Declared load profile	XL	Efficiency class	A	Water heating energy efficiency	$\eta_{wh}$	99	%
Daily electricity consumption	Q <sub>elec</sub>	<b>7,700</b>	kWh	Daily fuel consumption	Q <sub>fuel</sub>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>1694</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.

Contact details

CTC AB, Näsvägen 8, SE-341 34 Ljungby Tel +46 372 88000

www.ctc.se

F-0137

231206



Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	138 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>134</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>3,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>2,93</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>4,28</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,0</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>5,21</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>6,45</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,3</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,23</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>3,1</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>1,57</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>4,1</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>2,09</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-13</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-22</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>na</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>na</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>2,9</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>na</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>na</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>4316</b>	kWh				

For heat pump combination heater:

Declared load profile	XL	Efficiency class		Water heating energy efficiency	$\eta_{wh}$	84	%
Daily electricity consumption	Qelec	<b>9,070</b>	kWh	Daily fuel consumption	Q <sub>fuel</sub>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>1995</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.



Model(s):	CTC EcoAir 708M + CTC EcoZenith i360		
Air-to-water heat pump:	Yes	Energy efficiency class:	-
Water-to-water heat pump:	No	Controller class:	VI
Brine-to-water heat pump:	No	Controller contribution:	4 %
Low-temperature heat pump:	No	Package efficiency:	171 %
Equipped with a supplementary heater:	Yes	Package efficiency class:	-
Heat pump combination heater:	Yes		

Parameters shall be declared for medium-temperature application, except for low-temperature heat pumps. For low-temperature heat pumps, parameters shall be declared for low-temperature application.

Item	Symbol	Value	Unit	Item	Symbol	Value	Unit
<b>Rated heat output (*)</b>	<i>P<sub>rated</sub></i>	<b>6</b>	kW	<b>Seasonal space heating energy efficiency</b>	$\eta_s$	<b>167</b>	%
Declared capacity for heating for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>				Declared coefficient of performance or primary energy ratio for part load at indoor temperature 20 °C and outdoor temperature T <sub>j</sub>			
T <sub>j</sub> = -7 °C	<i>P<sub>dh</sub></i>	<b>3,7</b>	kW	T <sub>j</sub> = -7 °C	<i>COP<sub>d</sub></i>	<b>3,63</b>	-
T <sub>j</sub> = +2 °C	<i>P<sub>dh</sub></i>	<b>2,3</b>	kW	T <sub>j</sub> = +2 °C	<i>COP<sub>d</sub></i>	<b>5,20</b>	-
T <sub>j</sub> = +7 °C	<i>P<sub>dh</sub></i>	<b>2,1</b>	kW	T <sub>j</sub> = +7 °C	<i>COP<sub>d</sub></i>	<b>6,74</b>	-
T <sub>j</sub> = +12 °C	<i>P<sub>dh</sub></i>	<b>2,4</b>	kW	T <sub>j</sub> = +12 °C	<i>COP<sub>d</sub></i>	<b>8,04</b>	-
T <sub>j</sub> = bivalent temperature	<i>P<sub>dh</sub></i>	<b>4,6</b>	kW	T <sub>j</sub> = bivalent temperature	<i>COP<sub>d</sub></i>	<b>2,89</b>	-
T <sub>j</sub> = operation limit temperature	<i>P<sub>dh</sub></i>	<b>3,6</b>	kW	T <sub>j</sub> = operation limit temperature	<i>COP<sub>d</sub></i>	<b>2,25</b>	-
For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>P<sub>dh</sub></i>	<b>4,4</b>	kW	For air-to-water heat pumps: T <sub>j</sub> = -15 °C (if TOL < -20 °C)	<i>COP<sub>d</sub></i>	<b>2,69</b>	-
Bivalent temperature	<i>T<sub>biv</sub></i>	<b>-13</b>	°C	For air-to-water heat pumps: Operation limit temperature	<i>TOL</i>	<b>-22</b>	°C
Cycling interval capacity for heating	<i>P<sub>cych</sub></i>	<b>NA</b>	kW	Cycling interval efficiency	<i>COP<sub>cyc</sub></i>	<b>NA</b>	-
Degradation co-efficient	<i>C<sub>dh</sub></i>	<b>0,98</b>	-	Heating water operating limit temperature	<i>WTOL</i>	<b>55</b>	°C
Power consumption in modes other than active mode				Supplementary heater			
Off mode	<i>P<sub>OFF</sub></i>	<b>0,015</b>	kW	Rated heat output (*)	<i>P<sub>sup</sub></i>	<b>2,4</b>	kW
Thermostat-off mode	<i>P<sub>TO</sub></i>	<b>0,015</b>	kW	Type of energy input <b>Electric</b>			
Standby mode	<i>P<sub>SB</sub></i>	<b>0,015</b>	kW				
Crankcase heater mode	<i>P<sub>CK</sub></i>	<b>0,000</b>	kW	For air-to-water heat pumps: Rated air flow rate, outdoors			
Other items				For water-/brine-to-water heat pumps: Rated brine or water flow rate, outdoor heat exchanger			
Capacity control	<b>Variable</b>			-	<b>2787</b>	<b>NA</b>	m <sup>3</sup> /h
Sound power level, indoors/outdoors	<i>L<sub>WA</sub></i>	<b>NA / 46</b>	dB	-	<b>NA</b>		m <sup>3</sup> /h
Annual energy consumption	<i>Q<sub>HE</sub></i>	<b>3484</b>	kWh				

For heat pump combination heater:

<b>Declared load profile</b>	<b>XL</b>	<b>Efficiency class</b>		<b>Water heating energy efficiency</b>	$\eta_{wh}$	<b>84</b>	%
Daily electricity consumption	<i>Q<sub>elec</sub></i>	<b>9,07</b>	kWh	Daily fuel consumption	<i>Q<sub>fuel</sub></i>	<b>NA</b>	kWh
Annual electricity consumption	AEC	<b>1995,4</b>	kWh	Annual fuel consumption	AFC	<b>NA</b>	GJ

Specific precautions and end of life information:

The packaging must be deposited at a recycling station or with the installation engineer for correct waste management. At the end of the product's life cycle, it must be sent correctly to a waste station or reseller offering a service of that type. It is of great importance that the product's refrigerant, compressor oil and electrical/electronic equipment are properly disposed of. Disposing of the product as household waste is not permitted.